

HYUNDAI PRODUCT LINE GUIDE

HYUNDAI FORKLIFT TRUCKS



 **HYUNDAI**
FORKLIFT



Hyundai Forklift Trucks

From our North American headquarters and parts depot located in suburban Atlanta, we provide dealer and product support, warranty administration, technical training and parts inventory and shipping functions.

Backed by the global research and development resources of Hyundai Heavy Industries, one of the world's most trusted industrial brands, Hyundai Forklift is a full-line supplier of high-performance forklifts, including diesel, electric- and LPG-powered models, from 2,200 to 55,000 lb (997 to 24,947 kg) capacity.





ELECTRIC FORKLIFTS



Photos may include optional equipment.



ELECTRIC FORKLIFTS



10/13/15BTR-9



15/18/20BT-9



20/25/30/32BC-9

Item		Three-Wheel Rear Drive			Three-Wheel Rear Drive			Four-Wheel Drive - Cushion				
Item		10BTR-9	13BTR-9	15BTR-9	15BT-9	18BT-9	20BT-9	20BC-9	25BC-9	30BC-9	32BC-9	
Identification	Model											
	Load capacity	lb	2,204	2,756	3,307	3,000	3,500	4,000	4,000	5,000	6,000	6,400
	Load center	in	24	24	24	24	24	24	24	24	24	24
Weights	Service weight	lb	5,302	5,798	6,261	6,889	7,419	7,716	9,270	9,733	10,736	11,199
	Axle loading, loaded front / rear	lb	6,382/1,124	7,363/1,191	8,322/1,246	9,098/1,098	10,141/1,246	10,803/1,323	11,539/2,141	13,261/1,984	15,104/2,247	15,898/2,357
	Axle loading, unloaded front / rear	lb	2,460/2,841	2,646/3,153	2,765/3,497	3,662/3,228	3,770/3,649	3,713/3,997	3,948/5,322	3,774/5,959	4,098/6,638	4,090/7,033
Wheels, Chassis	Tire Type	Super-elastic			Super-elastic			Solid rubber				
Dimension	Overhead guard height	in	79.5			81.3			88.0			
	Length to face of forks	in	65.2	68.9	71.3	74.2	77.8	79.1	84.6	86.8	92.3	92.3
	Overall width	in	39.0			42.3			43.7	43.7	44.0	44.0
	Turning radius	in	52.6	56.1	128.4	60.6	64.2	65.4	75.2	76.2	82.5	82.5
	Right-angle stacking aisle width 40 x 48 in*	in	117.9	121.4	123.6	127.0	130.6	131.9	138.9	141.6	147.8	147.8
Right-angle stacking aisle width 32 x 48 in*	in	122.7	126.2	128.4	131.9	135.4	136.8	148.3	149.3	155.6	155.6	
Performance	Travel speed loaded / unloaded	mph	7.8/8.1			9.9/10.6			10.6/11.2			
	Drive motor rating	kw	4.3*2			4.7*2			14			
	Pump (lift) motor rating	kw	9.0			14			17			
	Battery voltage	V/Ah	24/625	24/750	24/750	48/510	48/585	48/585	48/740	48/740	48/845	48/845
	Battery compartment (L/W/H)	in	32.7/12.9/24.7	32.7/17.2/24.7	32.7/19.3/24.7	38.7/21.8/25.0			39.8/30.4/22.8	39.8/30.4/22.8	39.8/34.3/22.8	39.8/34.3/22.8
Others	Type of drive control	AC			AC			AC				

*Allow six inches for safe distance when turning and stacking.



ELECTRIC FORKLIFTS



16/18/20B-9



22/25/30/32/35B-9



10/13BOP-7



40T-9 15P-9

Item		Four-Wheel Drive								Order Picker	Tugger		
Model		16B-9	18B-9	20B-9	22B-9	25B-9	30B-9	32B-9	35B-9	13BOP-7	40T-9	15P-9	
Identification	Load capacity	lb	3,200	3,500	4,000	4,400	5,000	6,000	6,400	7,000	3,000	8,000	3,300
	Load center	in	24	24	24	24	24	24	24	24	-	-	
	Service weight	lb	6,945	7,220	7,672	8,918	9,502	10,472	10,880	11,442	6,398	-	-
Weights	Axle loading, loaded front / rear	lb	9,259/1,213	9,872/1,316	10,692/1,389	11,905/1,863	13,073/1,940	14,859/2,227	15,609/2,326	16,733/2,425	1,872/7,525	-	-
	Axle loading, unloaded front / rear	lb	3,494/3,450	3,534/3,686	3,638/4,034	3,373/5,181	3,792/5,710	4,277/6,195	4,332/6,548	4,343/7,099	3,583/2,813	-	-
Wheels, Chassis	Tire Type	Super-elastic				Super-elastic, Pneumatic				Polyurethane	Polyurethane		
Dimension	Overhead guard height	in	81.3				87.8				89.0	56.3	
	Length to face of forks	in	80.1	83.5	83.9	90.0	90.4	98.0	98.5	102.0	74.0	-	-
	Overall width	in	42.3	43.5	43.5	47.2	47.2	47.2	47.2	49.2	41.3	43.3	
	Turning radius	in	63.7	70.7	71.3	76.3	76.3	84.6	85.2	86.8	71.6	61.8	84.4
	Right-angle stacking aisle width 40 x 48 in*	in	132.0	134.9	135.7	143.2	143.2	150.7	151.3	153.0	133.5	-	-
Right-angle stacking aisle width 32 x 48 in*	in	137.6	140.7	141.5	149.7	149.7	157.8	158.4	160.5	138.1	-	-	
Performance	Travel speed loaded / unloaded	mph	9.9/10.6				10.6/11.2				9.5/10.0	5.0/6.2	
	Drive motor rating	kw	4.7*2				7.0*2	7.0*2	7.0*2	7.0*2	5.2	4.0	
	Pump (lift) motor rating	kw	14				17				10.6	-	-
	Battery voltage	V/Ah	48/510	48/585	48/585	48/660	48/715	48/740	48/740	48/740	48/400	48/230	
	Battery compartment (L/W/H)	in	38.5/21.5/25.0	38.5/24.8/25.0	38.5/24.8/25.0	40.7/31.7/21.3	40.7/31.7/21.3	40.7/39.4/21.3	40.7/39.4/21.3	40.7/39.4/21.3	38.3/16.3/31.1	37.9/14.9/21.6	37.9/14.9/21.6
Others	Type of drive control	AC								AC	AC		

*Allow six inches for safe distance when turning and stacking.



ELECTRIC FORKLIFTS



22/25/30/35BH-9



40/45/50B-9

Item		Four-Wheel Drive - Pneumatic				Four-Wheel Drive - Pneumatic		
		22BH-9	25BH-9	30BH-9	35BH-9	40B-9	45B-9	50B-9
Identification	Model	22BH-9	25BH-9	30BH-9	35BH-9	40B-9	45B-9	50B-9
	Load capacity	lb 4,400	5,000	6,000	7,000	8,000	9,000	11,000
	Load center	in 24	24	24	24	24	24	24
Weights	Service weight	lb 10,042	10,384	11,310	12,357	15,113	16,193	17,207
	Axle loading, loaded front / rear	lb 12,963/1,929	13,977/1,918	15,955/1,969	17,756/2,317	21,050/2,881	23,052/3,062	24,983/3,225
	Axle loading, unloaded front / rear	lb 5,170/4,872	5,115/5,269	5,655 5,655	5,686/6,671	7,725/7,388	8,060/8,133	8,331/8,876
Wheels, Chassis	Tire Type	Super-elastic, Pneumatic				Super-elastic, Pneumatic		
Dimension	Overhead guard height	in 87.0	87.0	87.0	87.0	91.3		
	Length to face of forks	in 91.9	93.1	98.2	102.4	117.9	117.9	119.7
	Overall width	in 44.0				53.9	53.9	56.1
	Turning radius	in 74.6	75.8	80.9	84.4	105.1	105.1	106.5
	Right-angle stacking aisle width 40 x 48 in*	in 138.4	138.4	144.3	144.7	173.4	173.4	175.0
	Right-angle stacking aisle width 32 x 48 in*	in 145.4	145.4	151.6	152.1	181.3	181.3	182.9
Performance	Travel speed loaded / unloaded	mph 11.2/11.8				10.6/10.6		
	Drive motor rating	kw 8.0 x 2				10.0 x 2		
	Pump (lift) motor rating	kw 20				28		
	Battery voltage	V/Ah 80/500	80/500	80/600	80/600	80/700	80/700	80/700
	Battery compartment (L/W/H)	in 40.5/28.1/32.6	40.5/28.1/32.6	40.5/33.8/32.6	40.5/33.8/32.6	40.7/39.5/31.1	40.7/39.5/31.1	40.7/39.5/31.1
Others	Type of drive control	AC				AC		

*Allow six inches for safe distance when turning and stacking.

ELECTRIC FORKLIFTS



15/18/20/23BRP-9



15/18/20/25/30BR-9



14/16/20/25BRJ-9

Item		Pantograph Reach Forklift				Moving Mast Reach Forklift									
		15BRP-9	18BRP-9	20BRP-9	23BRP-9	15BR-9	18BR-9	20BR-9	25BR-9	30BR-9	14BRJ-9	16BRJ-9	20BRJ-9	25BRJ-9	
Identification	Model														
	Load capacity	lb	3,000	3,500	4,000	4,500	3,300	3,980	4,400	5,500	6,000	2,800	3,200	4,000	5,000
	Load center	in	24				24					24			
Operator Type		Standing				Standing					Seated				
Weights	Service weight	lb	8,781	7,408	7,727	8,600	5,223	5,199	5,642	6,537	7,207	6,980	7,185	8,375	8,873
	Axle loading, loaded front/rear	lb	7,143/4,639	7,031/3,878	7,762/3,964	8,576/4,524	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Axle loading, unloaded front/rear	lb	3,512/5,269	2,879/4,528	3,045/4,683	3,406/5,194	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Axle loading, reach-in, unloaded front/rear	lb					1,773/3,274	1,625/3,530	1,830/3,680	2,048/4,356	2,326/4,881	4,180/2,800	4,442/2,743	4,954/3,422	5,593/3,280
	Axle loading, reach-out, unloaded front/rear	lb					7,288/1,065	8,003/1,120	8,863/1,056	10,670/1,246	12,549/1,272	1,327/8,739	1,345/9,367	1,391/11,393	1,517/12,868
	Axle loading, reach-in, loaded front/rear	lb					5,569/2,784	5,620/3,503	6,484/3,435	7,180/4,736	8,746/5,077	3,554/6,512	3,871/6,841	4,200/8,587	5,229/9,153
Wheels, Chassis	Tire Type (load/drive/caster)	Polyurethane				Polyurethane/Solid rubber/Solid rubber					Polyurethane/Solid rubber/Solid rubber				
	Service brake	Electromagnetic brake				Disc	Disc	Disc	Disc	Disc	Electric	Disc	Disc	Disc	Disc
Dimension	Overhead guard height	in	95.0	95.0	95.0	95.0	89.0	89.0	89.0	90.3	90.3	83.3	83.3	84.1	84.1
	Reach stroke	in	42.8	23.3	23.3	23.3	17.6	26.2	26.2	31.8	34.5	19.8	21.8	21.4	27.2
	Outrigger inner dimension/BR, BRJ overall width (load end/drive end)	in	42.0	42.0	42.0	42.0	42.1	42.1	43.9/42.1	47.2	47.7/47.2	50.4/50.0	50.4/50.0	50.8/50.0	53.1/50.0
	Turning radius (in standard battery compartment)	in	73.1	65.6	67.4	71.6	62.8	69.9	69.9	78.0	81.8	64.5	66.3	68.6	74.2
Performance	Travel speed loaded/unloaded	mph	7.3/7.3				6.8/6.8	6.8/6.8	6.8/6.8	7.5/7.5	6.8/6.8	8.7/8.7			
	Hydraulic motor	kw	6.8				6					7.5			
	Pump (lift) motor rating	kw	16				14					14			
	Maximum battery voltage	V/Ah	36/1,085	36/775	36/930	36/1,085	48/335	48/335	48/365	48/365	48/365	48/420	48/420	48/560	48/560
	Battery compartment	Varies based on compartment type					39.1/14.9/22.9					48.1/11.1/31.0	48.1/11.1/31.0	48.1/13.9/31.0	48.1/13.9/31.0
Others	Type of drive control	AC				FET Inverter					AC MOSFET				

LPG FORKLIFTS



Photos may include optional equipment.



LPG FORKLIFTS



15/18/20L-7M



25/30/33L-7A



25/30/33L(G)-7M



35/40/45/50/60/70L-7A

Item		LPG Forklifts - Pneumatic						L-7M: LPG Forklift G-7M: Dual Fuel Forklift(LPG/Gasoline)			LPG Forklifts - Pneumatic						
Model		15L-7M	18L-7M	20L-7M	25L-7A	30L-7A	33L-7A	25L(G)-7M	30L(G)-7M	33L(G)-7M	35L-7A	40L-7A	45L-7A	50L-7A	60L-7A	70L-7A	
Identification	Load capacity	lb	3,000	3,500	4,000	5,000	6,000	6,500	5,000	6,000	6,500	7,720	8,820	9,920	11,020	13,230	15,430
	Load center	in	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Service weight	lb	5,930	6,305	6,712	8,152	9,231	9,765	9,328	9,224	9,762	12,330	13,590	14,500	15,530	19,537	20,790
Weights	Axle loading, loaded front/rear	lb	8,024/1,212	8,031/1,334	9,656/1,468	11,995/1,657	13,830/2,001	14,839/2,186	12,131/1,709	13,882/1,956	14,894/2,145	18,000/2,040	20,050/2,360	21,810/2,620	23,620/3,020	29,010/3,750	32,110/4,110
	Axle loading, unloaded front/rear	lb	2,623/3,307	2,528/3,777	2,438/4,274	3,268/4,884	3,472/5,759	3,446/6,320	3,481/4,848	3,503/5,721	3,475/6,287	5,810/6,520	6,110/7,480	6,130/8,380	6,200/9,320	8,800/10,650	8,5230/12,270
Wheels, Chassis	Tire size, front		6.5 x 10-12PR	6.5 x 10-12PR	6.5 x 10-12PR	7.0 x 12-12PR	8.15 x 15-14PR	8.15 x 15-14PR	7.0 x 12-12PR	8.15 x 15-14PR	8.15 x 15-14PR	8.25 x 15-14	7.50 x 16-12	7.50 x 16-12	7.50 x 16-12	8.25 x 15	8.25 x 15
	Tire size, rear		5.0 x 8-10PR	5.0 x 8-10PR	5.0 x 8-10PR	6.0 x 9-10PR	6.50 x 10-12PR	6.50 x 10-12PR	6.0 x 9-10PR	6.50 x 10-12PR	6.50 x 10-12PR	7.0 x 12-12	7.0 x 12-12	7.0 x 12-12	7.0 x 12-14	8.25 x 15	8.25 x 15
Dimension	Overhead guard height	in	83.1	83.1	83.1	85.8	85.8	85.8	85.8	85.8	85.8	86.6/88.2/92.1	86.6/88.2/92.1	86.6/88.2/92.1	98.4	98.4	
	Length to face of forks	in	87.9	89.1	90.9	102.1	106	107.6	102.6	106.0	107.6	120.9	123.0	125.4	128.0	140.6	142.5
	Overall width	in	42.1	42.1	42.1	45.7	48.4	48.4	45.7	48.4	48.4	53.9	68.5	68.5	68.5	82.2	82.2
	Ground clearance, loaded, under mast	in	4.7	4.7	4.7	5.1	5.7	5.7	5.1	5.7	5.7	6.7	6.1	6.1	6.1	7.7	7.7
	Turning radius	in	78.7	79.8	81.1	90.5	94.4	95.8	91.1	94.4	95.8	110.5	112.6	114.4	116.0	130.7	132.7
Performance	Travel speed, unloaded	mph	12.5		11		11.6	11.6	10.5	11.5	11.5	14.8	14.2	14.2	14.2	14.0	14.0
	Engine manufacturer / model		HYUNDAI/L4KB			HYUNDAI/L4KB			GM/3.0L			GM/4.3L					
	Engine power		50			59			64.1			95.2			94		
	Rated speed	1/min	2,450			2,300			2,400			2,300					
	No. cylinder / cubic capacity	/cc	4/2,359			4/2,359			4/2,967			6/4,294					
	Service brake		Wet Disc			Wet Disc			Wet Disc			Wet Disc					

LPG FORKLIFTS



15/18/20LC-7M



25/30LC-7A



25/30LC-7M

Item		LPG Forklifts – Pneumatic, Cushion						
		15LC-7M	18LC-7M	25LC-7A	30LC-7A	25LC-7M	30LC-7M	
Identification	Model							
	Load capacity	lb	3,000	3,500	5,000	6,000	5,000	6,000
	Load center	in	24	24	24	24	24	24
Weights	Service weight	lb	6,235	6,673	8,274	9,352	8,479	9,337
	Axle loading, loaded front/rear	lb	8,093/1,448	8,913/1,618	12,129/1,655	14,019/1,947	12,405/1,585	18,975/1,975
	Axle loading, unloaded front/rear	lb	2,425/3,809	2,284/4,389	2,983/5,291	3,029/6,323	3,245/5,234	2,983/6,353
Wheels, Chassis	Tire size, front		18 x 6 - 12	18 x 6 - 12	21 x 7 - 15	21 x 8 - 15	21 x 7 - 15	21 x 8 - 15
	Tire size, rear		14 x 5 - 10	14 x 5 - 10	16 x 6 - 10.5	16 x 6 - 10.5	16 x 6 - 10.5	16 x 6 - 10.5
Dimension	Overhead guard height	in	84.4	84.4	81.9	81.9	81.9	81.9
	Length to face of forks	in	82.4	83.7	91.1	93.3	91.1	93.3
	Overall width	in	38.6	38.6	41.9	43.7	41.9	43.7
	Ground clearance, loaded, under mast	in	3.5	3.5	3.5	3.5	3.5	3.5
	Turning radius	in	74.5	75.6	81.9	83.8	81.9	83.8
Performance	Travel speed unloaded	mph	10.5	10.5	10.1	10.1	9.9	9.8
	Engine manufacturer / model		MMC/2.0L		HYUNDAI/L4KB		GM/3.0L	
	Engine power		48		60		64	
	Rated speed	1/min	2,300		2,300		2,400	
	No. cylinder / cubic capacity	/cc	4/1,997		4/2,359		4/2,967	
	Service brake		Mechanic/Hydraulic		Wet Disc		Wet Disc	



DIESEL FORKLIFTS



Photos may include optional equipment.



DIESEL FORKLIFTS



15/18/20D-9



25/30/33D-9 35DA-9



35/40/45D-9 50DA-9

Item		Diesel Forklifts											
		15D-9	18D-9	20D-9	25D-9	30D-9	33D-9	35DA-9	35D-9	40D-9	45D-9	50DA-9	
Identification	Model	15D-9	18D-9	20D-9	25D-9	30D-9	33D-9	35DA-9	35D-9	40D-9	45D-9	50DA-9	
	Load capacity	lb 3,000	3,500	4,000	5,000	6,000	6,500	N/A	7,700	8,800	9,900	11,000	
	Load center	in 20	20	20	24	24	24	24	24	24	24	24	
Weights	Service weight	lb 2,811	2,971	3,111	8,572	9,440	10,055	N/A	13,082	14,295	15,212	16,131	
	Axle loading, loaded front/rear	lb 3,678/633	4,046/675	4,421/690	12,273/1,802	14,054/1,997	15,007/2,324	N/A	17,948/2,851	20,078/3,034	21,806/3,327	23,541/3,611	
Wheels, Chassis	Axle loading, unloaded front/rear	lb 1,228/1,583	1,187/1,784	1,147/1,964	3,527/5,044	3,675/5,765	3,589/6,466	N/A	5,756/7,326	6,144/8,148	6,131/9,081	6,124/10,005	
	Tire size, front	6.50 x 10-14PR			7.0 x 12-14PR	28 x 9-15,14PR	28 x 9-15,14PR	N/A	8.25 x 15-14PR	7.50 x 16-12PR			
Dimension	Tire size, rear	5.0 x 8-8PR			6.50 x 10-14PR	6.50 x 10-14PR	6.50 x 10-14PR	N/A	7.0 x 12-12PR		7.0 x 12-14PR		
	Overhead guard height	in 83.1	83.1	83.1	85	85.8	85.8	N/A	87.0	87.0	87.0	87.0	
	Length to face of forks	in 87.6	88.7	90.1	102.6	105.4	107.6	N/A	127.0	127.0	129.0	130.0	
	Overall width	in 42.1	42.1	42.1	47.2	48.3	48.3	N/A	54.0	96.0	96.0	96.0	
	Ground clearance, loaded, under mast	in 4.7	4.7	4.7	5.1	5.7	5.7	N/A	6.7	6.1	6.1	6.1	
	Turning radius	in 78.9	79.9	81.3	92.2	95.0	97.0	N/A	116.0	116.0	118.0	118.0	
Performance	Travel speed, unloaded	11.4			11.5	12.4	12.4	N/A	16.5	16	15.9	15.9	
	Service brake	Wet Disc				Wet Disc				Wet Disc			
	Engine manufacturer/model	Daedong/3F183T				KUBOTA/V3307				CUMMINS/QSF3.8			
	Engine power	50				67				101			
	Rated speed	1/min 2,300	2,300				2,200						
	No. cylinder / cubic capacity	3/1,826				4/3,331				4/3,726			
	Fuel consumption rate	g/h 45	0.85			0.9	0.95	1.61		1.64	1.69	1.72	

DIESEL FORKLIFTS



50/70/80D-9



110/130/160D-9



180/250D-9

Item		Diesel Forklifts								
		50D-9	70D-9	80D-9	110D-9	130D-9	160D-9	180D-9	250D-9	
Identification	Model									
	Load capacity	lb	11,023	15,432	17,400	25,000	29,000	35,000	40,000	55,116
	Load center	in	24	24	24	24	24	24	36	47
Weights	Service weight	lb	19,599	23,091	25,591	35,880	37,459	43,746	57,528	81,617
	Axle loading, loaded front/rear	lb	26,792/3,730	33,347/5,011	38,034/5,384	52,823/7,308	59,029/7,090	70,568/8,453	88,110/9,447	126,274/92,030
	Axle loading, unloaded front/rear	lb	9,940/9,557	9,757/13,166	11,310/14,484	17,758/18,120	17,611/19,848	20,825/22,919	28,332/29,542	41,110/40,508
Wheels, Chassis	Tire size, front		8.25 x 15-14PR	8.25 x 15-14PR	9.0 x 20-14PR	10.0 x 20-16PR	10.0 x 20-16PR	12.0 x 20-18PR	12.0 x 20-20PR	14.0 x 24-32PR
	Tire size, rear		8.25 x 15-14PR	8.25 x 15-14PR	9.0 x 20-14PR	10.0 x 20-16PR	10.0 x 20-16PR	12.0 x 20-18PR	12.0 x 20-20PR	14.0 x 24-32PR
Dimension	Overhead guard height	in	102.2	102.2	103.9	115.9	115.9	117.3	117.7	126.9
	Length to face of forks	in	138.5	144.3	156.3	179.9	180.3	200.0	220.3	250.5
	Overall width	in	82.2	82.2	86.4	96.5	96.5	98.3	100.0	120.1
	Ground clearance, loaded, under mast	in	7.7	7.7	9.8	9.8	9.8	9.8	9.6	11.8
	Turning radius	in	130.5	135.3	145.7	171.3	171.3	192.7	205.5	230.9
Performance	Travel speed, unloaded	mph	21.1	20.9	21.7	22.1	22.1	21.9	23.3	19.6
	Service brake		Wet Disc		Wet Disc	Wet Disc		Wet Disc	Wet Disc	
	Engine manufacturer/model		CUMMINS/QSF3.8		CUMMINS/QSF3.8	CUMMINS/QSB6.7		BENZ (MTU)	CUMMINS QSL	
	Engine power		101	101	101	164	164	164	282	274
	No. cylinder / cubic capacity	/cc	4/3,800		4/3,800	6/6,690		6/7,700	6/8,898	
	Fuel consumption rate	g/h	2.14	2.19	2.25	2.93	3.01	3.20	3.91	6.60



HYUNDAI
B03

B02

HYUNDAI
B01

HYUNDAI
A05

HYUNDAI
A03

HYUNDAI
A02

HYUNDAI
A01

HYUNDAI
A04



Hyundai Forklift North America

Supported by more than 150 dealer and branch locations across the United States and Canada, Hyundai Forklift is committed to offering innovative equipment solutions, exceptional parts availability, fast delivery and timely technical support to our dealers and their customers throughout North America.





Hyundai Construction Equipment Americas, Inc.
6100 ATLANTIC BOULEVARD NORCROSS GA 30071 U.S.A
TEL (1) 678-823-7777 / FAX (1) 678-823-7778